BLIKAČKY SADA FORCE POINT USB ART. 45445

OBSAH BALENÍ



Art. 45445



Art. 452107



Art. 4516904

SPECIFIKACE

Blikačky sada FORCE POINT USB přední+zadní
Počet módů: 2 včetně indikace stavu baterie
Svítivost v lumenech: *36 Lm přední bílá/ 5 Lm zadní červená
Výdrž baterie: *4-8 h
Doba nabíjení: *2-3 h
Typ baterie: Lithium polymer/ 3.7V/ 240mAh/ integrovaná
Počet nabíjecích cyklů: *500
Typ čočky: 0,5 W
Hmotnost světla včetně držáku: 27 g
Hmotnost baterie: 5 g
IPX stupeň ochrany: IPX4
Provozní teplota: -10˚ C – 40˚ C
USB nabíjení včetně indikace
Stranově nastavitelný držák
Materiál: plast SAN/ ABS
Velikost: délka 33,5 mm, šířka 24,5 mm, výška 13 mm
* Maximální naměřené hodnoty za ideálních podmínek testu.

INSTALACE



NABÍJENÍ BATERIE



1. 2.

OVLÁDÁNÍ/ VÝDRŽ BATERIE

3 funkce svícení: stálé svícení (4h)
3 funkce blikání: blikání (8h)
přepínání mezi funkcemi/ vypnutí: krátký stisk tlačítka



V případě slabé kapacity baterie indikátor svítí červeně.
Indikátor světla svítí červeně během nabíjení.
Při plně nabité baterii červené světlo nesvítí.

Světlo nabíjejte pouze přiloženým USB kabelem / nabíječkou, jiný kabel/ nabíječka může způsobit poškození světla. Kabel/ nabíječku po nabíjení vždy odpojte od světla a elektrické sítě, skladujte a používejte na suchém místě v interiéru. Nenechávejte při nabíjení bez dozoru. Baterie se nenabíjí, pokud je počítač v režimu spánku.
Po nabíjení vždy zajistěte USB vstup světla krytkou. Baterie se při nabíjení může zahřívat. K prodloužení životnosti doporučujeme častější nabíjení na menší kapacitu než 1 plné nabití. Vyhněte se ultra-rychlému nabíjení s vysokou kapacitou. Před dlouhodobým skladováním akumulátor nabijte (baterie se musí nejméně 1 x za 6 měsíců dobít). Nenabíjejte, ani jinak nepoužívejte poškozené světlo.

UPOZORNĚNÍ

Vyvarujte se přímého pohledu do zapnutého světla. Směr světla na řídítkách/ helmě vždy nastavte co nejvíce dolů, zabráníte tak nežádoucímu osvětlení ostatních chodců a cyklistů. Vždy sejměte světlo při čištění a skladování kola ve venkovních prostorách (chraňte před deštěm a sněhem). Světlo vždy vypněte, pokud ho nepoužíváte.
Nedotýkejte se hliníkového těla zapnutého světla – může být horké. Světlo používejte na dobře větraném místě v exteriéru, hrozí riziko přehřátí.
Zabudovaný tepelný senzor sníží výkon světla při přehřátí. Světlo je možné opět použít při běžné provozní teplotě. Světlo může rušit funkci ostatních elektronických přístrojů (např. cyklistické tachometry). Kapacita baterie se může snížit na cca 70-80% po 300-500 nabíjecích cyklech. Kapacita baterie se snižuje při nižší okolní teplotě.
Nevystavujte světlo ani baterii vysoké teplotě +40°C (např. na horkém místě v autě), dlouhodobě nízkým teplotám pod 0°C, vysoké vlhkosti a přímému slunečnímu záření.
Skladujte na chladném, suchém místě mimo dosah dětí, zdrojů tepla a hořlavých materiálů. Chraňte před ohněm a vznětlivými látkami.
Neponořujte světlo pod vodu. Světlo je voděodolné, lze ho tedy používat za mírného deště. Při silném dešti doporučujeme světlo uschovat na suchém místě.
Neomývejte vodou a nepoužívejte agresivní čističe. Nerozebírejte ani jinak neupravujte světlo, baterii a příslušenství. Po uplynutí životnosti zlikvidujte světlo a baterie ekologicky dle platné vyhlášky. Nabíjení více než 5V může zničit baterii.

ZÁRUKA

Záruka nemůže být uplatněna na poškození způsobené vystavením nadměrným teplotám, mechanickým poškozením, neodborným servisním zásahem, úpravami, neodbornou montáží nebo nesprávným použitím.

Specifikace a provedení mohou být změněny bez předchozího upozornění. Aktuální verzi manuálu naleznete na stránkách dodavatele www.FORCE.cz.

FORCE.BIKE

22 PAP

Dodavatel / Importer / поставщик
KCK Cyklosport-Mode s.r.o., Bartošova 348, 765 02 Otrokovice-Kvítkovice, CZ
www.kckcyklosport.cz, , www.force.bike
Země původu Čína / Made in China / страна происхождения Китай

BLINKING LIGHTSET FORCE POINT USB ART. 45445

PACKAGE CONTENTS



Art. 45445



Art. 452107



Art. 4516904

SPECIFICATION

blinking lightset FORCE POINT USB front w+rear red
Number of light modes: 2 with battery indicator
Light intensity in lumens: *36 Lm front white / 5 Lm back red
Battery life: *4-8 h
Charging time: *2-3 h
Battery type: Lithium polymer/ 3.7V/ 240mAh/ integrated
Number of charging cycles: *500
Beam type: 0,5W
Light weight including holder: 27 g
Battery weight: 5 g
IPX protection level: IPX4
Operating temperature: -10° C – 40° C
USB charging with indication
Side adjustable holder
Material: plastic SAN / ABS
Size: lenght 33,5 mm, width 24,5 mm, height 13 mm
* Maximum measured value under ideal test conditions.

INSTALLATION



BATTERY CHARGING



1.



2.



OPERATION/ BATTERY LIFE

3 functions lighting: lighting (4h)
3 functions flashing: flashing (8h)
function switch lighting/ flashing: short press of button
switch off the light: short press of button



In case of low battery the red indicator lights.
The light indicator lights red during charging.
When the battery is fully charge, the light is off.

Charge the light only with the supplied USB cable / charger, another cable / charger can cause light damage. Always unplug the cable/ charger after charging, store and use in a dry place indoors. Do not leave unattended when charging. The battery does not charge when the computer is in sleep mode.
Always ensure the USB port of the light by the lid after charging. The battery may get warm when charging. Several part cycles are better for the battery that 1 full cycle.
Avoid ultra-fast high capacity charging. Charge the battery before long term storage (the battery must be recharged at least once every 6 months).
Do not charge or otherwise use the damaged light.

NOTICE

Do not look directly into the light. To prevent from blinding oncoming riders and walkers always adjust the light angle downwards.
Always dismount the light while cleaning the bicycle and storage outside (protect from rain and snow). Switch the light off if not used.
Do not touch the the alloy light body in use – might be hot. Use the light in well ventilated place outdoors – risk of overheating.
Integrated overheat protection sensor will automatically decrease the light output in case of overheat. The light can be used again at standard operating temperatures.
Light and battery can cause interference of other electrical devices (computers). Battery capacity can be reduced to approximately 70-80% after 300-500 charging cycles.
Battery capacity decreases at lower temperature. Do not expose the light or the battery to a high temperature of + 40 ° C (hot place in the car),
low temperatures below 0 ° C, high humidity and direct sunlight. Store in a cool, dry place, keep away from children, heat source and inflammable material.
Protect from fire and inflammable substances. Do not submerge in water. Light is water-resistant, it can be used in light rain. During heavy rain,
it´s reccomended to store on dry place. Do not clean with water or agressive cleaners. Do not disassemble or otherwise modify the light, battery and accessories.
Dispose the light and battery ecologically according to valid regulations. Do not charge over 5V.

WARRANTY

Warranty does not apply to damage due to high and low temperatures, physical damage resulting from abuse, improper repair, improper fit, alternations of the fixture or improper use.

Specifications and designs may be changed without prior notice. The current version of the manual can be found on the supplier's website www.FORCE.cz.

FORCE.BIKE

22 PAP

Dodavatel / Importer / поставщик
KCK Cyklosport-Mode s.r.o., Bartošova 348, 765 02 Otrokovice-Kvítkovice, CZ
www.kckcyklosport.cz, , www.force.bike
Země původu Čína / Made in China / страна происхождения Китай